

## Cold Water – Electric – Direct Drive

**Pump:**

- Forged brass manifold (Nickel plated brass on 2MUH models)
- Thermal and safety relief valves
- Low pressure detergent injector

**Motor:**

- Totally enclosed fan-cooled electric motor with thermal overload protection
- 35-foot, 15-amp power cord (20-amp on CD-1502 models) with ground fault circuit interrupter, GFCI

**Frame:**

- Powder coated steel mounting plate with center balanced lift and four rubber isolators

**Unit Includes:**


- Variable high/low pressure nozzle (3MUH models)
- 15° high/low pressure nozzle (2MUH models)
- 25-foot x 3/8-inch non-marking high pressure hose with quick connects
- Professional-grade insulated trigger gun with safety lock-off

**Limited Warranties:**

- 1 year electric motor
- 7 year AR and General pumps

**Certification:**

- CSA Certified - US and Canada



CD-1502-2MUH

The lightweight and portable design of the CD Electric Series makes it a great choice for all-purpose cleaning around the home or small business. So easy to use almost anyone can tackle these cleaning jobs.

| MODEL NUMBER  | PSI  | GPM | HORSEPOWER/MOTOR        | PUMP    | MI-T-M NO. | UNLOADER            | PLUG TYPE  | LANCE | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|---------------|------|-----|-------------------------|---------|------------|---------------------|------------|-------|--------------------|----------|---------|
| CD-1002-3MUH  | 1000 | 2.0 | 1.5 HP, 120V, 1Ø, 12.5A | AR      | 3-0362     | Adjustable pressure | NEMA 5-15P | 36in. | 20x11.5x14in.      | 70 lb.   | 58 lb.  |
| CD-1002-2MUH* | 1000 | 2.0 | 1.5 HP, 120V, 1Ø, 12.5A | General | 3-0278     | Adjustable pressure | NEMA 5-15P | 36in. | 20x11.5x14in.      | 71 lb.   | 66 lb.  |
| CD-1502-3MUH  | 1500 | 2.0 | 2.0 HP, 120V, 1Ø, 17.0A | AR      | 3-0362     | Adjustable pressure | NEMA 5-20P | 36in. | 20x11.5x14in.      | 76 lb.   | 70 lb.  |
| CD-1502-2MUH* | 1500 | 2.0 | 2.0 HP, 120V, 1Ø, 17.0A | General | 3-0278     | Adjustable pressure | NEMA 5-20P | 36in. | 20x11.5x14in.      | 76 lb.   | 70 lb.  |

\*Pump accepts incoming water up to 175°F

**Accessories & Options:**

| PART NUMBER | DESCRIPTION     | FITS MODELS    | PART NUMBER | DESCRIPTION                       | FITS MODELS |
|-------------|-----------------|----------------|-------------|-----------------------------------|-------------|
| 18-0370     | Rotating nozzle | CD-1502 models | 50-0161     | High pressure detergent injector  | All models  |
| 18-0371     | Rotating nozzle | CD-1002 models | CX-0030     | 50-ft. x 3/8-in. non-marking hose | All models  |