

Cold Water – Electric – Belt Drive

Pump:

- External bypass system allows more water into the system to protect from heat build-up
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

Motor:

- Totally enclosed fan-cooled electric motor with thermal overload protection
- 10-foot power cord

Frame:

- Powder coated steel frame and base plate with 1¼-inch tube handles
- Convenient gun/wand holder and hose wrap
- Totally enclosed belt guard
- 13-inch flat-free tires

Unit Includes:


- Quick connect nozzles - 0°, 15°, 25° and 40°
- 50-foot x ¾-inch non-marking high pressure hose with quick connects
- Professional-grade insulated trigger gun with safety lock-off

Limited Warranties:

- 1 year Mi-T-M unloader (CW-4004-1ME3)
- 1 year electric motor
- 7 year General pump (CW-4004-1ME3 and CW-5004-0ME3)
- 10 year General pump (CW-2405, CW-3004 and CW-3005 models)



CW-3004-4ME3



Perfect for cleaning heavily soiled equipment located inside commercial facilities. Use it to clean grimy floors and concrete walls of garages and service shops. It is even a great tool to keep indoor pools free from dirt, mold and mildew.

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	Mi-T-M NO.	UNLOADER	PLUG TYPE	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-2405-4ME1	2400	4.6	7.5 HP, 230V, 1Ø, 32.0A	General	3-0202	Factory preset	NEMA 6-50P	36in.	46x28x30in.	345 lb.	333 lb.
CW-2405-4ME3*	2400	4.6	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	3-0202	Factory preset	NEMA L15-30P	36in.	45.5x32.5x30in.	355 lb.	343 lb.
CW-3004-4ME1	3000	3.5	7.5 HP, 230V, 1Ø, 32.0A	General	3-0202	Factory preset	NEMA 6-50P	36in.	46x28x30in.	350 lb.	338 lb.
CW-3004-4ME3*	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	3-0202	Factory preset	NEMA L15-30P	36in.	45.5x32.5x30in.	403 lb.	301 lb.
CW-3005-0ME1	3000	4.8	10.0 HP, 230V, 1Ø, 41.5A	General	3-0202	Factory preset	NEMA 6-50P	36in.	45.5x32.5x30in.	470 lb.	396 lb.
CW-3005-0ME3*	3000	4.8	10.0 HP, 230V, 3Ø, 26.0A or 10.0 HP, 460V, 3Ø, 13.0A	General	3-0202	Factory preset	NEMA 15-50P	36in.	45.5x32.5x30in.	450 lb.	376 lb.
CW-4004-1ME3	4000	3.9	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	3-0075	Mi-T-M, factory preset	NEMA 15-50P	48in.	45.5x32.5x30in.	505 lb.	431 lb.
CW-5004-0ME3*	5000	4.0	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	3-0261	Factory preset	NEMA 15-50P	48in.	45.5x32.5x30in.	505 lb.	431 lb.

*460V motors available as options.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0005	36-in. insulated dual lance	2400 to 3000-PSI models
851-0317	50-ft. x ¾-in. non-marking hose	CW-5004-0ME3	CX-0057	460V on 15.0-HP, 3-phase models	CW-4004-1ME3 & CW-5004-0ME3
851-0338	50-ft. x ¾-in. non-marking hose	2400 to 4000-PSI models	CX-0062	460V on 10.0-HP, 3-phase model	CW-3005-0ME3
AW-8400-0021	Low pressure detergent injector	All models	CX-0093	Stationary option	CW-2405 & CW-3004 models
CX-0003	460V on 8.0-HP, 3-phase models	CW-2405-4ME3 & CW-3004-4ME3	CX-0094	Stationary option	CW-3005, CW-4004 & CW-5004 models